

Netzwerkkarte PCI 10/100 MBit TP-Link TF-3239DL

- 10/100M PCI Adapter
 - One 10/100Mbps Auto-Negotiation RJ45 port
 - Supports drivers for most popular OS
-
- Complies with IEEE 802.3, IEEE 802.3u standards
 - Provides 32-bit PCI interface, PCI2.1, PCI2.2
 - One 10/100Mbps Auto-Negotiation RJ45 port
 - Supports Full Duplex and Half Duplex transfer modes
 - Supports IEEE 802.3x flow control for Full Duplex mode
 - Provides diagnostic software
 - One LED indicator for monitoring link/activity
 - Supports drivers for NetWare 3.x, 4.x, Windows 98, Windows Me, Windows NT4.0, Windows 2000, Windows XP, Linux 2.4.x

Standards	IEEE 802.3, IEEE 802.3u
Bus Type	32-bit 33MHz PCI 2.1/2.2
Port	1 10/100Mbps Auto-Negotiation RJ45 Port
Network Media	10BASE-T: UTP category 3, 4, 5 cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m) 100BASE-TX: UTP category 5, 5e cable (maximum 100m) EIA/TIA-568 100Ω STP (maximum 100m)
LED Indicators	Link/Act
Dimensions (W x D x H)	134 x 121 x 22 mm (5.3 x 4.8 x 0.9 in.)
Environment	Operating Temperature: 0°C~40°C (32°F~104°F) Storage Temperature: -40~70°C (-40°F~158°F) Operating Humidity: 10%~90% non-condensing Storage Humidity: 5%~95%, non-condensing
Operating System	Windows 98/ME/NT4.0/2000/2003/XP, Netware, Linux

