

# Netzwerk Switch 16-Port, Gbit, 1U rack TP-Link TL-SG1016

- 16 10/100/1000M RJ45 ports.
  - Supports MAC address self-learning and auto MDI/MDIX.
  - Standard 19-inch rack-mountable steel case.
- 
- Fully compliant with IEEE 802.3 (10BASE-T), IEEE 802.3u (100BASE-TX) and IEEE 802.3ab (1000BASE-T)
  - 16 10/100/1000Mbps Auto-negotiation Ethernet Ports
  - All ports support Full/half duplex transfer mode for 10Mbps/100Mbps and Full duplex transfer mode for 1000Mbps
  - Supports Auto-MDI/MDIX function
  - Supports IEEE 802.3X flow control for full-duplex mode and back pressure flow control for half-duplex mode
  - Store and forward Switching scheme

Standard		IEEE 802.3、IEEE 802.3u、IEEE 802.3ab
Port		16 10/100/1000M Auto-Negotiation RJ45 ports supporting Auto MDI/MDIX
Network Media		10Base-T : Cat. 3 or above UTP 100Base-TX : Cat.5 UTP 1000Base-T: Cat.5 UTP
Filter and transmission rate		10Mbps : 14880pps 100Mbps : 148800pps 1000Mbps: 1488000pps
LED Indicator	Each port	Link/Act, 10M/100M, 1000M
	Others	Power
Dimension (L x W x H)		17.3 x 7.1 x 1.7 in.(440 x 180 x 44 mm)
Environment		Operation Temperature : 0°C-40°C ; Store Temperature : -40°C-70°C Operation Humidity : 10%-90% RH Non-condensing ; Store Humidity : 5%-90% RH Non-condensing
Power		Input: 100-240VAC, 50/60Hz

