

PCI I/O Controller Karte Firewire (IEEE 1394a– 3x extern, 1x intern)



Brief

- Firewire 1394a 3-Ports External + 1-Port Internal with 400Mb/s
-

Features

- Firewire 1394a Ports: External x 3 and Internal x 1
-

Specification

General

- PCI 32-Bit 33MHz Interface
- Compliant with PCI Specification Revision 2.2
- Support PCI Bus-Master Access
- Fully Plug & Play compatible
- Driver supported MS Windows 98SE/Me/2000/XP/Server 2003/XP 64-bit/Vista, Linux or Mac OS

Firewire 1394a interface

- 1394 OpenHCI Specification v1.0 and v1.1 compliant
 - Support IEEE 1394-1995 Standard for High Performance Serial Bus 1.0 with 1394a-2000
 - Data transfer rate: 100/200/400Mbps supported
 - External port: 1394a 6-Pin x 3
 - Internal port: 1394a 6-Pin x 1 (Shared)
-

System Requirement

- PC or Macintosh computer with one 32-bit PCI slot
 - Supported OS
-

Included

- FireWire 1394a Controller Card
- IEEE-1394a 6-Pin to 6-Pin Cable (Optional)
- ULEAD Video Studio Software (Optional)
- User manual

