

# PCI I/O Controller Karte Firewire + USB (je 2x extern + 2x intern)

---



## Brief

- USB 2.0 + Firewire 1394a Combo PCI Card
- 

## Features

- USB 2.0 Ports: External x 2 and Internal x 2
  - FireWire 1394a Ports: External x 2 and Internal x 1 (Shared)
  - Occupies One PCI Slot. Designed for PC Requiring USB and FireWire Interface Add-On But with Only One Vacant PCI Slot
- 

## Specification

### General

- PCI 32-Bit 33MHz Interface
- Compliant with PCI Specification Revision 2.2
- Support PCI Bus-Master Access
- Fully Plug & Play compatible
- Driver supported MS Windows 98SE/Me/2000/XP/Server 2003XP 64-bit/Vista, Mac OS

### FireWire 1394a Interface

- 1394 OpenHCI Specification v1.0 and v1.1 Compliant
- Support IEEE 1394-1995 Standard for High Performance Serial Bus 1.0 with 1394a-2000
- Data transfer rate: 100/200/400Mbps supported
- External port: 1394a 6-Pin x 2
- Internal port: 1394a 6-Pin x 1 (Shared)

### USB 2.0 Interface

- Compliant with Universal Serial Bus (USB) Specification Revision 2.0
  - Compliant with Enhanced Host Controller Interface (EHCI) Specification Revision 1.0
  - Compliant with Universal Host Controller Interface (UHCI) Specification Revision 1.1
  - Backward compatible with USB 1.1 Specification
  - Data transfer rate: High Speed 480Mbps, Full Speed 12Mbps, and Low Speed 1.5Mbps supported
  - Connects up to 127 USB devices simultaneously on each port
  - External port: USB-A x2
  - Internal port: USB-A x1 and Pin Header Port x 2
- 

## System Requirement

- PC or Macintosh computer with one 32-Bit PCI slot
  - Supported OS
- 

## Included

- PCI USB 2.0 & FireWire 1394a Combo Card
- IEEE-1394a 6-Pin to 6-Pin Cable (Optional)
- ULEAD Video Studio Software (Optional)
- User manual
- Software CD Driver

